

# MID 25~40KTL3-X

- The maximum efficiency is up to 98.8%
- 40% compact and lighter
- AFCI function optional
- Self-consumption monitoring
- Touch key and OLED display
- Type II SPD on DC and AC side



P O W E R  
- I N G O  
T O M O -  
R R O W O



Datasheet	MID 25KTL3-X1	MID 30KTL3-X	MID 33KTL3-X	MID 36KTL3-X	MID 40KTL3-X
<b>Input data (DC)</b>					
Max. recommended PV power (for module STC)	37500W	45000W	49500W	54000W	60000W
Max. DC voltage	1100V				
Start Voltage	250V				
Normal Voltage	600V				
MPPT voltage range	200-1000V				
No. of MPP trackers	3	3	3	4	4
No. of PV strings per MPP tracker	2				
Max. input current per MPP tracker	26A				
Max. short-circuit current per MPP tracker	32A				
<b>Output data (AC)</b>					
AC nominal power	25000W	30000W	33000W	36000W	40000W
Max. AC apparent power	27700VA	33300VA*	36600VA	39600VA	44000VA
Nominal AC voltage (range*)	220V/380V, 230V/400V (340-440V)				
AC grid frequency (range*)	50/60 Hz (45-55Hz/55-65 Hz)				
Max. output current	40A	50.5A	55.5A	60.0A	66.6A
Adjustable power factor	0.8leading...0.8lagging				
THDI	<3%				
AC grid connection type	3W+N+PE				
<b>Efficiency</b>					
Max. efficiency	98.8%				
European efficiency	98.5%				
MPPT efficiency	99.9%				
<b>Protection devices</b>					
DC reverse polarity protection	Yes				
DC Switch	Yes				
AC/DC surge protection	Type II / Type II				
Insulation resistance monitoring	Yes				
AC short-circuit protection	Yes				
Ground fault monitoring	Yes				
Grid monitoring	Yes				
Anti-islanding protection	Yes				
Residual-current monitoring unit	Yes				
String monitoring	Optional				
Anti-PID function	Optional				
AFCI protection	Optional				
<b>General data</b>					
Dimensions (W / H / D)	575/420/225mm				
Weight	30kg				
Operating temperature range	- 35°C ... +60°C				
Noise emission (typical)	≤50dB(A)				
Nighttime power consumption	<1W				
Topology	Transformerless				
Cooling	Smart air cooling				
Protection degree	IP66				
Relative humidity	0-100%				
Altitude	4000m				
DC connection	H4/MC4(Optional)				
AC connection	Cable gland+OT terminal				
Display	OLED+LED/WIFI+APP				
Interfaces: RS485 / USB / WIFI / GPRS / RF / LAN	Yes/Yes /Optional/Optional/Optional/Optional				
Warranty: 5 years / 10 years	Yes /Optional				
CE, VDE0126, Greece, EN50549, C10/C11, UTE C 15-712, IEC62116, IEC61727, IEC 60068, IEC 61683, CEI0-21, CEI0-16, N4105, TOR Erzeuger, G98/G99, G100, AS/NZS 3100, AS4777, UNE21 7001, UNE206007, PO12.2, KSC8565					

\* For Belgium C10/C11 and VDE-AR-N4105, MID 30KTL3-X max. output power is limit to 30KVA.

\* The AC voltage range and frequency range may vary depending on specific country grid standard. All specifications are subject to change without notice.